

Resilient Care and Maintenance

You can protect your Mannington Resilient Floor by following these easy guidelines.

- Use a doormat outside each entrance to your home to prevent dirt, sand, grit, and other substances such as oil, asphalt, and driveway sealer from being tracked onto your floor. Use non-staining mats on your floor. Do not put rubber-backed, latex-backed, or coco-fiber mats on your floor because they will stain or damage the surface.
- To minimize potential staining from asphalt tracking, we suggest you use a latex-based driveway sealer.
- Close your curtains or blinds where extreme sunlight hits the floor. A combination of heat and sunlight causes most home furnishings, including resilient floors, to fade or discolor.
- Support furniture with wide-bearing, non-staining floor protectors. Ideally, the protectors should be at least one inch in diameter, made of non-pigmented, hard plastic, and rest flat on the floor. Non-staining felt protectors are also acceptable. Casters with a minimum 3/4" flat surface width or floor protectors are recommended for all moveable furniture. Make sure any metal protectors are rust-proof. Replace your narrow dome furniture rests with wide-bearing ones.
- If you need to move heavy furniture and/or appliances, such as your refrigerator, across the floor, always use strips of wood or hardboard runways to protect the floor. Always use runways even if you have an appliance dolly, or even if the heavy objects are equipped with wheels or rollers.

Here are some simple things you can do to keep your Mannington Resilient Floor looking like new:

Initial Maintenance (within 24 hours of installation)

- Keep traffic light during the first 24 hours so adhesive can dry properly
- If the floor has been seamed, avoid stepping on the seam sealer for 24 hours so it can dry undisturbed
- Avoid scrubbing or washing floor for at least three days after installation. Spot clean floor avoiding all seams
- When moving heavy furniture or appliances across the floor, always use wood or hardboard runways to protect the floor

Routine Maintenance (daily/weekly as needed)

- Sweep your floor regularly (at least once a week) to remove loose dirt.
- Prevent stains by wiping spills promptly.
- Occasional mopping with Mannington Award Series® Cleaner (available from your retailer) is recommended when dirt builds up and sweeping alone is not sufficient. Use a solution of 2 to 3 capfuls of Award Series® Cleaner (or clear, non-sudsy ammonia) in one gallon of warm water. Using more than the recommended amount of cleaning solution may leave a dulling film. Do not use soap or detergent products as they will leave a dulling film. Rinsing is not required when using Mannington Award Series® Cleaner, but if time permits, rinsing will provide the best care and highest shine.
- All high-gloss floors will lose shine over time. To restore gloss, apply Mannington Award Series® Polish. Do not use wax. Do not buff. Be sure to thoroughly clean, rinse, and allow the floor to dry completely prior to applying polish.
- Mannington NatureForm® Collections are low-gloss floors. Use polish or "mop and shine" products only if you wish to make the floor shiny.
- After several applications of polish, an occasional stripping and reapplication of polish may be necessary. This may also be necessary for excessive dirt and grime build-up. We recommend the use of

Mannington Award Series® Heavy Duty Cleaner and Stripper. After thorough cleaning, rinsing, and drying, apply Mannington Award Series® Polish to restore the shine. High traffic areas may require more than one application of polish. Allow polish to dry "tack-free" between coats.

- **Caution:** Resilient floors can be slippery when wet. Use extreme caution when walking on a wet floor.

Resilient Stain Solver

Mannington Resilient Floors offer excellent stain resistance, and most spills will wipe off quickly and easily with a clean cloth. Removing certain stains takes a little extra effort. Here are some guidelines before you begin:

- Start with the first procedure listed.
- Only do the procedures necessary to resolve the problem. Always use a clean white cloth for wiping up stains, and turn it frequently to avoid spreading the stain.
- Rinse with clean water and allow area to dry between procedures.
- For items not covered by the following chart, call Mannington Consumer Services at 1-800-FLOOR-US (1-800-356-6787).

Stain/Problem	Procedure
Foods/Beverages	<p>If a gummy substance, scrape with off with a dull knife.</p> <p>Scour using Mannington Award Series® Heavy Duty Cleaner and Stripper and a nylon pad or stiff bristle brush.</p> <p>Saturate a clean white cloth with bleach solution, cover stain and allow to stand for no more than 1 hour.</p>
Tar, Oil, Asphalt, Grease, Paint (oil-based), Wax	<p>Scrape excess off with dull knife.</p> <p>Scour using Mannington Award Series® Heavy Duty Cleaner and Stripper and a nylon pad or stiff bristle brush.</p> <p>Wipe with a clean white cloth dampened with lighter fluid, painter's naphtha, or isopropyl alcohol.</p>
Scuffs, Marks, Scratches	<p>Scour using Mannington Award Series® Heavy Duty Cleaner and Stripper and a nylon pad or stiff bristle brush.</p> <p>Wipe with a clean white cloth dampened with lighter fluid, painter's naphtha, or isopropyl alcohol.</p>
Minor Cuts, Burns, Gouges	<p>Limit traffic over damaged area, cover with masking tape, contact your retailer or Mannington for advice.</p>
Lipstick, Antiseptics	<p>Scrape excess off with dull knife.</p> <p>Scour using Mannington Award Series® Heavy Duty Cleaner and Stripper and a nylon pad or stiff bristle brush.</p> <p>Wipe with a clean white cloth dampened with lighter fluid, painter's naphtha, or</p>

isopropyl alcohol.

Saturate a clean white cloth with bleach solution, cover stain and allow to stand for no more than 1 hour.

Rust Scour using Mannington Award Series® Heavy Duty Cleaner and Stripper and a nylon pad or stiff bristle brush.

Saturate a clean white cloth with bleach solution, cover stain and allow to stand for no more than 1 hour.

Crayon, Ink, Permanent Marker, Hair Dye Scour using Mannington Award Series® Heavy Duty Cleaner and Stripper and a nylon pad or stiff bristle brush.

Wipe with a clean white cloth dampened with lighter fluid, painter's naphtha, or isopropyl alcohol.

Caution Mineral spirits, lighter fluid, painter's naphtha, and isopropyl alcohol are flammable liquids. Please follow precautions listed on the container.